



Product Information

Construction:	Prima Coated PET Acid Free
Main Application:	This product is suitable for internal and external use for display; including glass office partitions, architectural design, etc.
Adhesive:	25 ± microns pressure sensitive solvent base acrylic (Clear removable)
Shelf Life:	Up to 2 years
Storage Conditions:	Stored up to 25°C and up to 50% relative humidity in original packaging
Features:	Thick PET liner for increased stability
Inks:	UV ink receptive coating
UV Treated:	Yes
Finish:	Gloss
Core:	76mm
Suitable for:	UV Flatbed and Roll to Roll Printers

Durability

 Up to 2 years*



For additional information on this product please use the above QR Code.

Thickness

PET Thickness:	36 ± microns
Adhesive Thickness:	25 ± microns
Total Thickness:	61 ± microns
Liner Thickness:	125 ± microns PET Polyester

Standard Stock Sizes

Codes	Standard sizes	Core	Adhesive
Gloss S49CRP125T/50	1530mm x 50m	76mm	Clear Removable

* Outdoor life will vary depending on installation technique, location and relative position to the sun.

V1.2

PLEASE NOTE – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.

ALC

www.alclaminating.com

Australian Laminating Company

Pty Ltd

76 NORTH VIEW DRIVE
SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400
F: +61 (0)3 9312 7455
SALES@ALCLAMINATING.COM