

BannerVue SL Data Sheet

Product Code: BVPL30SL

As at 26 June 2018

Applications	Non-adhesive interior mounted graphics to flat building windows and glass doors including refrigerated, for POP/POS, retail applications and shop/business signage. Also suitable for re-locate and/or re-use type requirements for poster size graphics (<1 sqm). To adhere to transparent surfaces, use OptiTape. Can also be used as a pull up/retractable banner film. Refer to the Recommended Applications Fact Sheet.
Makeup	Flexible perforated black (no adhesive) / white (printable side) matt PET film and single layer non-perforated white PET liner.
Vinyl Thickness	200 microns, approx.
Release Liner	50 microns, approx.
Adhesive	No adhesive layer. Use OptiTape around all edges to interior mount film to window.
Perforation Size and Pattern	1.5mm, 30% / 70% open/closed areas.
Standard Widths/Lengths	1370mm x 30m on 76mm core.
Dimensional Stability	Excellent. No shrinkage in X and Y axes. Test method FINAT TM14.
Application Temperatures	Refer to OptiTape technical data sheet.
Service Temperatures	-20°C to +100°C without tape, refer to OptiTape technical data sheet.
Expected Lifetime Interior	3 years.
Water & Humidity Resistance	Good – when interior mounted.
Storage Stability	1 year shelf life when stored out of direct sunlight at 23°C & 50% relative humidity.
Printing	Refer to the Ink Compatibility Fact Sheet. Compatible with solvent (including mid and eco), latex. Print image on white side. Testing recommended before production to determine appropriate profile settings.
Out Gassing	3 to 5 days when suspended vertically in ventilated area. Trim after out gas period.
Installation	<p>For transparent surfaces: Refer to the Surface Preparation Instructions and OptiTape data sheet. For graphics larger than 1 sqm, use full width OptiTape and laminate permanent adhesive (side A) to entire printed graphics using cold press laminator. At job site, remove BannerVue liner and side B liner of OptiTape. Wet apply to interior surface of a clean glass surface. For poster size graphics (<1m²), apply side A 25mm OptiTape around all edges to printed image, do not overlap in the corners. At job site remove BannerVue liner, then remove side B liner of OptiTape. Dry apply to clean glass surface.</p> <p>For retractable stands: Trim to dimensions appropriate for the stand. Mount bottom and top edges of trimmed film in accordance to manufacturer's instructions.</p>
Removal	Remove by peeling from surface. For poster size graphics (<1m ²), remove and discard tape. Re-apply graphic later with new 25mm OptiTape.
Warranty and Disclaimer	12 months from date of sale to distributor. Refer to the Warranty Statement.

The information in this data sheet is presented for reference and illustration of general product characteristics only. The information does not constitute a representation or warranty relating to the suitability or fitness for a particular application or otherwise create guarantees of product performance. **In all cases, purchasers should independently determine, prior to use, the suitability of this product for their specific application.**