

PRODUCT DATA SHEET



165 DOUBLE SIDED TAPE Double Sided Adhesive Coated Polyester

Product Features:

- * Excellent plasticiser migration resistance.
- * Offers a secure bond under high temperatures.
- * Good resistance to solvents, chemicals, UV and heat.
- * Exceptional bonding performance to low surface energy products.
- * Used to mount ABS plastics in Automotive industry.
- * Laminating and mounting of EPDM and rubber materials.
- * Also used to fix decorative trim in Furniture industry.

Product Specifications:

* Adhesive:	Solvent based Acrylic
* Backing:	Polyester
* Total thickness:	0.2mm
* Liner:	White paper
* Colour:	Transparent
* Shear strength:	PSTC-7 Over 48 hrs with 1kg loading on 25mm x 25mm
* Peel Adhesion:	PSTC-3 1.8kg per 25mm
* Temperature resistance:	-20 to 180 deg C.
* Maximum width:	960mm

NOTE: When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations issued on HUSKY TAPE CONVERTING products, has been based on research and is believed to be reliable, but does not constitute a warranty. All HUSKY TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product for the buyer's purpose.