

# JV100-160



PROFESSIONAL HIGH PERFORMANCE PRINTER

64"

## Expert Printing Made Easy

The JV100-160 is an affordable professional-grade eco-solvent roll-based model. Perfect for high-quality fine art reproduction to vehicle wrap printing and more.

- Available in 64" with print speeds up to 677 Sq Ft/Hr
- Eco-solvent: 4 color and 8 color options including Orange and Light Black inks
- NEW Dot Adjustment System (DAS) automatically aligns to ensure consistent quality and repeatability
- Nozzle Check Unit (NCU), automatically monitors printhead performance and detects clogged nozzles
- The Nozzle Recovery System (NRS), automatically substitutes unproductive nozzles, avoiding unnecessary downtime and poor image quality
- NEW, easier to use RIP software, RasterLink7, included; reduces RIP time by 25%

For best results, always use Mimaki original inks.

# Mimaki® JV100-160

<b>Printhead</b>	Two staggered on-demand
<b>Print Resolutions</b>	360 dpi, 540 dpi, 600 dpi, 720 dpi, 900 dpi, 1080 dpi, 1,200 dpi
<b>Print Speed (4 Color Mode)</b>	677.05
<b>Maximum Print Area</b>	63.3" (1610.0 mm)
<b>Maximum Media Width</b>	63.8 (1620 mm)
<b>Maximum Media Thickness</b>	up to 0.04" (1 mm)
<b>Maximum Media Weight</b>	up to 99.2 lbs
<b>Ink Type</b>	U.S. & Canada- AS5 eco-solvent: C, M, Y, K, Lc, Lm, Lk, Or SS21 eco-solvent: C, M, Y, K, Lc, Lm, Lk, Or
<b>Ink Package Size</b>	600ml or 2000ml
<b>Interface</b>	1000 Base-T Ethernet cable or USB2.0 cable
<b>Power Supply</b>	AC100~120V/ 200~240V±10%, 50/60Hz±1Hz
<b>Operational Environment</b>	Temperature 20° – 30°C Humidity: 35 – 65 % RH (Non condensing)
<b>Dimensions (W × D × H)</b>	3,775mm (12.38ft) or more (Machine size: 2,775mm(9.1ft)) 2,700mm or more (Machine size: 700mm(2.29ft))
<b>Weight</b>	166kg (366lb) (Leg unit: 25kg)(55lb) (Printer unit: 141kg) (310lb)

PROFESSIONAL HIGH PERFORMANCE PRINTER

64"

Please visit us at: [www.mimakiusa.com](http://www.mimakiusa.com)

Mimaki USA, Inc.  
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2020, Mimaki USA, Inc.

Rev. 10/22/21