

 graphic  
art mart™

  
JV330-160/130



## GIVE YOUR CREATIVITY A GLOW UP

High quality and high productivity with unimaginable added value and unparalleled ease of use...

The 330 series of the new generation have been designed and developed from the ground up with a casing to pursue image quality and productivity befitting a flagship mode I and new values that assist in saving work.

### Unparalleled improvement in droplet placement accuracy

Rigidity of the chassis has been increased to approximately 230% of our conventional product to improve the levelness of platen (ejection surface). Difficult-to-control ink droplets with a minimum size of 3pl are dispensed accurately through the evolution of waveform control technology.

### Banding suppression by the new drop technology, “Mimaki Weaving Dot Technology”

“Mimaki Weaving Dot Technology (MWDT)” significantly enhances the productivity of the staggered head arrangement, making the banding caused by slight stagger adjustment errors and individual head differences less noticeable.

### Higher image quality despite low-pass printing due to improved single-line resolution

Improved single-line resolution and increased number of nozzles results in higher density of dots per pass, allowing for better image quality even in low-pass printing through the evolution of waveform control technology.



☎ 1300 426 278

✉ [sales@gamart.com.au](mailto:sales@gamart.com.au)

📍 [gamart.com.au](http://gamart.com.au)

📧 [subscribe to our newsletter](#)

**Specifications:**

Item	JV330-130	JV330-160	
Print head	On-demand piezo head (2 staggered printheads)		
Print resolution	600 / 800 / 900 / 1200 dpi		
Head gap	3 levels by manual (2.0 mm / 2.5 mm / 3.0 mm)		
Ink	Type	SS21 / BS4	
	Color	SS21:C, M, Y, K, Lc, Lm, Lk, Or, W: BS4: C, M, Y, K	
	Capacity	2L ink pack (SS21 White: 500 ml Ink pack only)	
Ink circulation	Circulation in damper MCTv2		
Max.Printable width	1,360 mm (53.5 in)	1,610 mm (63.4 in)	
Media	Max. Width	1,370 mm (53.9 in)	
	Outer dia.	250 mm or less	
	Max. Load capacity	3 rolls (with the Media changer)	
	Weight	One roll: 45 kg (99.2 lb.) or less / Three rolls total: 90 kg (198.4 lb.) or less	
	Core dia.	2 / 3 inch	
Interface	Ethernet 1000 BASE-T(Recommended) / USB 2.0 Hi-speed		
Power	Main unit : Single phase AC100 - 120V±10% 12A AC200 - 240V±10% 6A 50/60 Hz ±1 Hz x 2 pcs.		
Power consumption	Max.1,440W or less x2 / Min.4.5W or less (Sleep mode)		
Operational environment	Temperature : 20 - 30 degC (68 - 86 degF) Humidity : 35 - 65% Rh (Non condensing)		
	Guaranteed accuracy temperature : 20 - 25 degC (68 - 77 degF)		
	Dust level : 0.15 mg/m3 or less (Equivalent to general office)		
Dimensions (WxDxH)	2,920 mm x 1,215 mm x 1,305 mm (115.0 x 47.8 x 51.4 in)	3,170 mm x 1,215mm x 1,305 mm (124.8 x 47.8 x 51.4 in)	
Weight	358 kg (789.2 lb)	368 kg (811.3 lb)	

**Supplies:**

Item	Color	Item code	Item code
SS21 GREENGUARD Gold Certified ink	Cyan	SPC-0588C	2L ink pack
	Magenta	SPC-0588M	
	Yellow	SPC-0588Y	
	Black	SPC-0588K	
	Light Cyan	SPC-0588LC	
	Light Magenta	SPC-0588LM	
	Orange	SPC-0588OR	
	Light Black	SPC-0588LK	
	White	SS21-W-50	
BS4	Cyan	BS4-C-2L	500ml ink pack
	Magenta	BS4-M-2L	2L ink pack
	Yellow	BS4-Y-2L	
	Black	BS4-K-2L	
Maintenance Liquid 14		ML014-Z-22	220 ml cartridge
Cloth Wiper G Kit		SPC-0919	

**Installation Space:**

	JV330-130	JV330-160
Width	3,920 mm (154.3 in) or above	4,170 mm (164.2 in) or above
Depth	4,050 mm (159.4 in) or above	

