



Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-UV, EUV-PR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacture's name: Roland DG Corporation

Address: 1-6-4 Shinmiyakoda, Kita-ku, Hamamatsu-shi,

Shizuoka-ken, 431-2103

JAPAN

Phone: + 81-53-484-1224 Fax: + 81-53-484-1226

Australian Importer/Supplier: Roland DG Australia Pty Ltd
Address: Unit 14/25 Frenchs Forest Road

English French Storest Road

Frenchs Forest, NSW, 2086, Australia

Phone: + 61 2 9975 0000

New Zealand Importer/Supplier: Aarque Group Ltd Address: 2a Waipareira Ave

Henderson, Auckland, 0610, New Zealand

Phone: + 64 837 2144

E-mail Address: support@rolanddg.com.au

Revised date: 19 April 2019

1.4. Emergency telephone: Australia - + 61 2 9975 0000

New Zealand - 0800 76 74 66

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Acute toxicity (oral) Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 1 Sensitisation — Skin Category 1B Reproductive toxicity Category 2 Specific target organ toxicity — Repeated exposure Category 1 Hazardous to the aquatic environment — Acute Hazard Category 1 Hazardous to the aquatic environment — Chronic Hazard Category 1

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal word Danger

Hazard Statement(s): Combustible liquid. Harmful if swallowed.

Causes skin irritation.



ECO-UV, EUV-PR

Causes serious eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Response IF ON SKIN: Wash with plenty of soap and water.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Others: No information.



3. Composition/information on ingredients

Chemical nature: mixture

Chemical nature. Illixture					
Composition	CAS No.	EC No.	EU regis- tration No.	% By Weight	Classification EC No.1272/2008
Benzyl acrylate	2495-35-4	219-673-9	01-2120772339- 44	50-60	Skin Irrit. 2: H315 Skin Sens. 1B: H317 Aquatic Acute 1: H400
Morpholine, 4-(1-oxo-2-propenyl)-	5117-12-4	418-140-1	N/A for the moment	10-20	Acute Tox. 4: H302 Skin Sens. 1: H317 Eye Dam. 1: H318
1-vinylhexahydro-2H- azepin-2-one	2235-00-9	218-787-6	01-2119977109- 27	5-10	Acute Tox. 4: H302 Acute Tox. 4: H312 Eye Irrit. 2A: H319 Skin Sens. 1B: H317
Diphenyl(2,4,6- trimethylbenzoyl) phosphine oxide	75980-60-8	278-355-8	01-2119972295- 29	10-20	Repr. 2: H361
Poly[oxy(methyl-1,2- ethanediyl)], .alpha., .alpha.', .alpha.''-1,2,3- propanetriyltris[.omega [(1-oxo-2-propenyl)oxy]]-	52408-84-1	500-114-5	N/A for the moment	0-1	Eye Irrit. 2: H319 Skin Sens. 1: H317
Hexamethylene diacrylate	13048-33-4	235-921-9	01-2119484737- 22	0-1	Skin Irrit. 2: H315 Skin Sens. 1: H317
Inhibitors	C. B. I.	C. B. I.	N/A for the moment	0-1	Skin Sens. 1: H317 Aquatic Chronic 4: H413

ECO-UV, EUV-PR

4. First aid measures

4.1. Description of first aid measures

In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open Eyes:

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Inhalation:

oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and

irritate nose, throat/respiratory system.

[†] C.B.I.: Confidential Business Information

[‡] For the full text of the H-Statements mentioned in this Section, see Section 16.





Ingestion: May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 70deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.



7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

ECO-UV, EUV-PR

7.3 Specific end use(s): Inkjet Printing

Roland

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

Hexamethylene diacrylate:

[Long term exposure] 24.5 mg/m³

[Short term exposure] no hazard identified

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide:

[Long term exposure] 3.5 mg/m³

[Short term exposure] no hazard identified

1-vinylhexahydro-2H-azepin-2-one:

[Long term exposure] 4.9 mg/m³

[Short term exposure] no hazard identified

Poly[oxy(methyl-1,2-ethanediyl)], .alpha., .alpha.', .alpha.'-1,2,3- propanetriyltris[.omega.-[(1-oxo-2-propenyl)oxy]]-.:

[Long term exposure] 3.7 mg/m³

[Short term exposure] no hazard identified

Morpholine, 4-(1-oxo-2-propenyl)-:

[Long term exposure] 132.24 mg/m³

[Short term exposure] 132.24 mg/m³

2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-:

[Long term exposure] 1.75 mg/m³

[Short term exposure] hazard unknown (no further information necessary)

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

In case ventilation is insufficient, employee must use NIOSH approved air purifying respiratory equipment. Use a half facepiece respirator (with goggles) or full face-piece respirator (without goggles) filtered with organic vapor cartridge. For emergency and other conditions where the exposure guideline may be exceeded, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self contained air supply. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Hand protection:

Employee must wear appropriate protective impervious gloves to prevent contact with the ink.





Recommended Chemical Protective Gloves are ethylene vinyl alcohol (EVA) Gloves and Laminate gloves. Laminate gloves are made by cutting and then heat-sealing patterns of various hand sizes from laminated sheets of EVA sealed between layers of polyethylene.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear safety glasses or chemical splash goggles.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Clear Liquid
Odour: Characteristic odour

Odour threshold: No data available pH: Not applicable Melting point/freezing point: No data available Initial boiling point and boiling range: No data available

Flash point: > 70deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available Vapor pressure: No data available

Vapor density: >1
Relative density: 1.0-1.1

Solubility(ies): Slightly soluble Partition coefficient: n-octanol/water: No data available Auto-ignition temperature: No data available No data available Decomposition temperature: No data available Viscosity: No data available Explosive properties: No data available Oxidizing properties: Volatile organic compounds (VOC) content: 36.0 grams/liter



9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

High temperatures and UV light may cause rapid polymerization.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

1-vinylhexahydro-2H-azepin-2-one (of one component of this product)

LD50 (Oral) 1114.0 LD50 (Dermal) 1700.0

Morpholine, 4-(1-oxo-2-propenyl)- (of one component of this product)

LD50 (Oral) 588.0

Serious eye damage/eye irritation:

Causes serious eye damage.

• Morpholine, 4-(1-oxo-2-propenyl)-

Causes serious eye irritation.

- Hexamethylene diacrylate
- 1-vinylhexahydro-2H-azepin-2-one
- Poly[oxy(methyl-1,2-ethanediyl)], .alpha., .alpha.', .alpha."-1,2,3- propanetriyltris[.omega.-[(1-oxo-2-propenyl)oxy]]-.

Skin corrosion/irritation:



Causes skin irritation.

- Hexamethylene diacrylate
- · Benzyl acrylate

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

- Hexamethylene diacrylate
- · Benzyl acrylate
- 1-vinylhexahydro-2H-azepin-2-one
- Poly[oxy(methyl-1,2-ethanediyl)], .alpha., .alpha.', .alpha."-1,2,3- propanetriyltris[.omega.-[(1-oxo-2-propenyl)oxy]]-.
 - Morpholine, 4-(1-oxo-2-propenyl)-
 - 2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

Suspected of damaging fertility or the unborn child.

• Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

no data available.

Specific target organ toxicity - repeat exposure, (STOT-RE):

Causes damage to organs through prolonged or repeated exposure.

• 1-vinylhexahydro-2H-azepin-2-one

May cause damage to organs through prolonged or repeated exposure.

• Morpholine, 4-(1-oxo-2-propenyl)-

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity:

Very toxic to aquatic life.

· Benzyl acrylate

Very toxic to aquatic life with long lasting effects.

· Benzyl acrylate

May cause long lasting harmful effects to aquatic life.



• 2,5-Cyclohexadien-1-one, 2,6-bis(1,1-dimethylethyl)-4-

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial and Local regulations. Do not flush to surface water or sanitary sewer system.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: 3082

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Environmentall hazardous substance, liquid, n.o.s. (Benzyl acrylate)

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: 9

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: III


14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Environmentally hazardous substance, liquid, n.o.s.

(Benzyl acrylate)

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions





and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

Australia Information:

Hazardous statement: Not classified as hazardous according to NOHSC criteria.

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H361: Suspected of damaging fertility or the unborn child.
- H372: Causes damage to organs through prolonged or repeated exposure.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- H413: May cause long lasting harmful effects to aquatic life.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.