

6582



Product description

TransferRite® 6582 is a medium tack application tape featuring a high grade saturated paper backing with specially formulated latex, pressure sensitive adhesive.

Applications

Can be used in sign shops for general purpose use as pre-space and decal transfer. Pre-spacing tape is designed to assist in the application and transfer of pressure sensitive decals that have been cut into letters and legends. 6582 is also recommended for striping and die cut logos and is best used for pre-spaced lettering from 5cm up to 31cm.

Technical information

Paper thickness (without adhesive)	83 µm
Adhesive thickness	23 µm
Total thickness	106 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	3.1 N/25mm (medium tack)
Core colour	yellow
Tensile strength	88 N/25mm
Elongation at break	3%
Shelf life (from time of manufacture)	30 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

