

# 1510



## Product description

---

TransferRite® 1510 is a medium tack application tape featuring a unique clear polypropylene film backing with a custom formulated latex adhesive for decal transfer and pre-spacing.

## Applications

---

Can be used in sign shops for general purpose use as pre-space and decal transfer. Pre-spacing tape is designed to assist in the application and transfer of pressure sensitive decals that have been cut into letters and legends. Ideal for lettering from 5cm up to 31cm. 1510 is invaluable where precise registration is required.

## Technical information

Film thickness (without adhesive)	98 µm
Adhesive thickness	8 µm
Total thickness	106 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	2.5 N/25mm (medium tack)
Core colour	yellow
Tensile strength	66 N/25mm
Elongation at break	600%
Shelf life (from time of manufacture)	24 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILTRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: [info@idealabi.com](mailto:info@idealabi.com) website: [www.idealabi.com](http://www.idealabi.com)

