

### 1. Product and Company Identification

D. I. (N.				
Product Name	: UVink LH-100 White			
Order No.	: LH100-W-BA/SPC-0597W/SPC-0659W			
Ink Ver.	:1			
General Use	: Inkjet Ink			
Product Description	: UV Inkjet Ink			
MSDS Number	: 031-38U06WC			
Manufacture				
Company Name	: Mimaki Engineering Co., Ltd			
Address	2182-3 Otsu, Shigeno, Tomi-shi, Nagano 389-0512 Japan			
Telephone No.	:+81-268-64-2413			
Importer / Distributor Established in USA				
Company Name	: MIMAKI USA. INC.			
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A			
Telephone No.	: +1-678-730-0100			
Emergency Telephone No.	: +81-268-64-2413			

#### 2. Hazards Identification

[GHS Classification]	
Physical Hazards	
Flammable Liquids	: Not classified
Health Hazards	
Acute Toxicity – Oral	Category 5
Acute Toxicity – Dermal	Category 5
Skin Corrosion / Irritation	Category 2
Eye Damage / Irritation	: Category 2A
Sensitization – Skin	Category 1
Toxic to Reproduction	Category 2
Environmental Hazards Hazardous to the Aquatic Environment - Acute Hazard	: Category 1

The above list does not include category being non-classifiable or not-applicable.



Product Name: UVink LH-100 White MSDS No. 031-38U06WC First issue: 2012/12/03 Revised: Page 2 of 10

## Material Safety Data Sheets

[GHS Label Elements]



Signal Word Warning

Hazard Statements

- H303 May be harmful if swallowed
- H313 May be harmful in contact with skin
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H361 Suspected of damaging fertility or the unborn child
- H400 Very toxic to aquatic life

**Precautionary Statements** 

[Prevention]

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing gas/mist.

- P264 Wash hands and eyes thoroughly after handing.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.

[Response]

- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P321 Specific treatment (see 4-Response).
- P362 Take off contaminated clothing and wash before reuse.
- P391 Collect spillage.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P332+P313 If skin irritation occurs: Get medical advice/attention.



Product Name: UVink LH-100 White MSDS No. 031-38U06WC First issue: 2012/12/03 Revised: Page 3 of 10

# Material Safety Data Sheets

P337+P313 If eye irritation persists: Get medical advice/attention. [Disposal] P501 Dispose of contents/container in accordance with

local/regional/national/international regulation (to be specified).

HMIS Rating (s	cale 0 – 4)	NFPA Rating (scale $0-4$ )		
Health = 2	2 Health	Health = 2		
Flammability= 1	1 Flammability	Flammability = 1		
Reactivity = $1$	1 Reactivity	Instability = 1	2 $1$	
Protective Equipment = G	G Protective Equipment	Special = None	XY	
			$\mathbf{v}$	

### 3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.	Chemical Formula
1	Acrylic ester	75-90	Registered	Trade secret
2	Diphenyl (2,4,6, -trimethylbenzoyl) phosphine oxide	10-15	Registered	Trade secret
3	Titanium dioxide	10-15	Registered	Trade secret
4	Additives	0.1-5	Registered	Trade secret

### 4. First Aid Measures

Inhalation	: If inhaled, immediately remove to fresh air and keep warm and
	calm.
	If breathing irregularly or not breathing, give artificial respiration
	and consult a doctor immediately.
Eye Contact	: Flush eyes thoroughly with water for at least 15 minutes.
	Remove contact lenses, if present and easy to do.
	Consult an ophthalmologist immediately.
Skin Contact	: Wash skin thoroughly with plenty of water.
	If on clothing, remove immediately contaminated clothing.
	The product don't evaporate therefore staying on the skin or clothing
	for a long time. If no washing or no taking off the clothing, it may

**Мітакі**.

Product Name: UVink LH-100 White MSDS No. 031-38U06WC First issue: 2012/12/03 Revised: Page 4 of 10

# Material Safety Data Sheets

	cause inflammation on the skin.
Ingestion	: Do not induce vomiting.
	If swallowed, keep calm and consult a doctor immediately.
	Keep from swallowing vomit.
Concise statement	: No relevant information found.
on the most	
important symptom	
Protection To First-Aiders	: Wear tools for appropriate protection.
	Ventilate.
	See section 7 and 8.
Note To Physician	: See section 7 and 8.

## 5. Fire Fighting Measures

Extinguishing Media	: Foam, carbon dioxide, dry chemical, water spray.
	Never splash water.
Hazard in fire	Avoid breathing combustion products.
Fire Fighting	: Wear tools for appropriate protection.
Instructions	Eliminate ignition sources.
	Stay upwind.
	Keep people away.
	Keep wetted with water surrounding equipment.
	Avoid discharge chemical substances to rivers and sewers.

### 6. Accidental Release Measures

Personal Precautions	<sup>:</sup> Wear tools for appropriate protection. Keep unnecessary and unprotected personnel from entering in vicinity of spill. Ventilate.
	See section 8.
Environmental	: Avoid discharge to rivers and environmental effects.
precautions	
Methods and materials	: Small spills:
for containment and	Absorb with nonflammable absorbent such as dry sand and dirt.
cleaning up.	Large spills:



Pump spills into a sealing container and remove to safe place.	
Use non-sparking equipment during recovery operation and ground	
equipment.	
See section 13, Disposal Considerations, for disposing of waste.	
: Prepare proper fire extinguishers and eliminate all sources of	
ignition in vicinity of spill.	
Avoid walking on the spills.	
Use safety tools to prevent sparks.	

### 7. Handling and Storage

Handling	: Handle in well-ventilated area.
	Prohibit use of fire, sparks and heat source.
	Use antistatic clothing and shoes.
	Ground equipment against electrostatics and use spark-proof tools.
	Keep from increasing of temperature for flammable substance.
	Use local exhaust system and proper protection if working in closed
	area.
	Use proper protection (gloves, masks, aprons, goggles, etc.)
Storage	: Keep container tightly closed, store at cool and aired place, open and
	handle carefully.
	Protect from light.
	Protect from heat/overheating.
	Avoid contact with peroxides or other free radical initiators.

### 8. Exposure Controls / Personal Protection

#### Exposure Limit Values

No	Chemical Name		TWA	STEL	Ceiling	Skin	SEN
	2000/39/EC	N.E.	N.E.	N.E.	N.E.	N.E.	
1	Titanium dioxide	ACGIH TLV	10mg/m3	N.E.	N.E.	N.E.	N.E.

**Exposure** Controls

Occupational Exposure Controls

**Engineering Controls** 

: Use explosion-proof equipment if handle in volume.

Use exhaust system to prevent vapor build-up.



Keep heat or fire sources from handling area. If working indoors, use proper equipment to protect workers from direct exposure or use local exhaust system to protect workers from exposure.

Personal Protection

**Respiratory Protection** 

: Wear protective masks for hazardous materials.

: Wear gloves resistant to organic solvents and chemicals.





Eye Protection

**Skin Protection** 



: Wear chemical goggles.

: Wear clothing to protect skin from direct exposure. Wear protective clothing resistant to chemicals.

### 9. Physical and Chemical Properties

Appearance - Physical State	: Liquid ( $25^{\circ}$ C)		
- Color	: White		
Odor	: Characteristic odor		
pH	: Not available		
Boiling Point / Boiling Range	: Not available		
Melting Point / Melting Range	: Not available		
Decomposition Temperature	: Not available		
Flash Point	$:130^{\circ}$ C		
Auto ignition temperature	: Not available		
Flammability (Solid, Gas)	: Not available		
Explosive Properties	: Not available		
Oxidizing Properties	: Not available		
Upper / Lower Flammability or	: Not available		
Explosive Limits			



Vapor Pressure	
Relative Density	$: 1.18(25^{\circ}C)$
Solubility	: Not available
Water Solubility	: Not available
Partition Coefficient (n-octanol / Water)	: Not available
Viscosity	: 22±3 mPa⋅s (25°C)
Vapor Density	: Not available
Evaporation Rate	: Not available
VOC	: Not available
Solvent content	: Organic solvents $\leq 0.5$ Wt%
water amount	$= 0.7 \mathrm{Wt}$

## 10. Stability and Reactivity

Reactivity	: Excessive heat and cold, sparks, ignition sources, light and high
	humidity. May result in polymerization.
Chemical stability	: Stable under the usual handling condition.
Possibility of hazardous	: See section reactivity.
reactions;	
Conditions to avoid	: Excessive heat and cold, sparks, ignition sources, light and high
	humidity.
Incompatible materials	: Oxidant, explosive substances, catalysts, alkaline, free radical
	initiators.
Hazardous	: To burn this product may be produce toxic gases such as CO and
decomposition products.	low-molecular-weight monomers.
Other	: Plastic and rubbers might be melted.

### 11. Toxicological Information

Acute Toxicity	Oral: Rats LD50 >2,000mg/kg: Category 5
	Dermal: Rabbit LD50 >2,000mg/kg: Category 5
Carcinogenicity	: Titanium dioxide
	IARC category 2B(Not possible to classify as a printing ink)
Others	: Not available



### 12. Ecological Information Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch. : Hazardous to the aquatic environment Ecotoxicity Acute hazard L(E)C50 <1.00mg/L: Category 1 Mobility : Not available Persistence and : Not available Degradability Bioaccumulative : Not available Potential Other Adverse Effects : Not available

#### 13. Disposal Considerations

- Have waste inks, containers and other materials disposed by licensed industrial waste disposer.
- Do not dump drainage flushed containers and equipment into sewers, on the ground.
- · Dispose of wastes from drainage or incineration, in compliance with the laws and regulations.
- · Adsorb to diatom earth and others to dispose waste inks, and use open incinerator.
- · Dispose of wastes by licensed industrial waste disposer to comply with the local laws and regulations.
- · Empty inks and other materials out of containers if disposed.

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

#### 14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

#### LAND TRANSPORT

ADR, RID UN Number

Name and description

: 3082

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.



	Class	: 9 Miscellaneous dangerous substances and articles
	Packing Group (PG)	: 111
	Hazard label	: 9
	Hazard Identification No.	: 90
	Classification code	: M6
	Transport category	: 3
	(Tunnel restriction code)	(E)
SEA TRANSPO	RT	
IMO/IMDG	UN Number	: 3082
	Proper shipping name	: ENVIRONMENTALLY HAZARDOUS
		SUBSTANCE,LIQUID, N.O.S.
	Class	: 9
	Packing Group (PG)	: Ш
	Hazard label	: 9
AIR TRANSPO	RT	
ICAO/IATA	UN Number	: 3082
	Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s.
	Class	: 9
	Packing Group (PG)	: Ш
	Hazard label	: 9
	Passenger and Cargo Limited	: Y964
	Quantity Packing Instructions	
	Packing Instructions (Passenger)	: 964
	Packing Instructions (Cargo)	: 964

#### 15. Regulatory Information

TSCA Status	: All components on TSCA INVENTORY.	
SARA Title		
Section 311/312	: Fire Hazard: No	
(40 CFR 370)	Pressure Hazard: No	
	Reactivity Hazard: No	
	Immediate Hazard: Yes	
	Delayed Hazard: Yes	
California Proposition 65	: This product contains, or may contain, trace quantities of a substance(s) known	
	to the state of California to cause cancer and/or reproductive toxicity.	



#### 16. Other Information

References International Chemical Safety Cards (ICSC)

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.

#### Revision history

Version	Date	Content
1.0	2012/12/03	First issue