

SOLVENT (ASGL2)

Asphalt graphics

1. Unbelievable Special Adhesive

Clean removal of glue (no residue) / easy installation .

2. No wrinkle

No shrinking and no wrinkle with premium aluminum base

3. Super-fast dry for solvent ink

1.5 times faster than other Alumi media.

SPECIFICATION

Base Material	Alumi base
Surface	Non PVC Embossed-Matte coating
TOTAL Caliper	300 μ m \pm 10
Liner Caliper (PAPER)	120gsm \pm 10
Width	1371mm (54")
Length	30.4 m (100ft)
Core	3"

TECHNICAL DATA

Adhesive (sus)	ASTM D3330	2700 \pm 50 gsm after 20min
		3100 \pm 50 gsm after 24hours

COMPATIBILITY

INK compatibility
Solvent, Eco-solvent, Mild-solvent, Latex, UV
Printer compatibility
Most solvent printing system & Latex printing system

NOTE

Printing condition	15~30°C (59~86°F) / Humidity 30~60%
Storage	Stored at 10~25°C (50~77°F) / Humidity 50~55% RH
Shelf Life	1 year stored in original package under above condition

APPLICATION

- * Floor and wall at outdoor & indoor
- * Retail shop event, temporary event, sponsorship targeted marketing, promotional events, way-finding, path to purchase, facility safety
- * Concrete, asphalt, brick, tile, terrazzo, marble, vinyl floor, stucco, cinder block, masonry

The above descriptions are tested by our own efforts based on international standard.

All descriptions can be changed as the case may be without any prior notification. No media warranty is implied.