



	100% Cotton	100% Polyester	Poly/Cotton Blends	Nylon	Lycra/Spandex	Leather	Sublimated Polyester	Home Iron Compatible	CPSIA Certified	Temperature	Pressure	Time (Seconds)	Peel Carrier
EasyWeed®										305° F/150° C	medium	10-15	hot or cold
EasyWeed® Extra										305° F/150° C	medium	10-15	hot or cold
EasyWeed® Electric										305° F/150° C	medium	15	hot or cold
EasyWeed® Stretch										320° F/160° C	firm	20	hot or cold
EasySubli®										311° F/155° C	medium	15	warm
EasyWeed® Sub Block										265° F/130° C	medium-firm	15	warm
EasyWeed® Adhesive										275° F/135° C	medium	5-10	hot
EasyReflective®										305° F/150° C	medium	15	warm
BlackBoard®										275° F/135° C	medium	15	warm
Glitter										320° F/160° C	firm	15-20	warm
Holographic										320° F/160° C	medium	10-15	cold
Metal										305° F/150° C	medium	10-15	cold
StripFlock® Pro										311° F/155° C	medium	15	warm
Brick® 600										311° F/155° C	medium-firm	15-20	cold
EasyPatterns®										305° F/150° C	medium	10-15	hot or cold

CPSIA means: This product has been independently lab tested and is Phthalate & Lead Compliant and is safe for application on children's products
Please test for compatibility on your garment before committing to production



	Ceramic	Painted Drywall	Glass	Metal	Plastic	Wood	Surface Characteristics	Thickness	Durability	Cutting Blade Recommendation
EasyPSV® Permanent							gloss finish	3 mils / 76.2 microns	3-5 year	45°
EasyPSV® Glitter							smooth gloss finish	3 mils / 76.2 microns	5 year	45°
EasyPSV® Etch							matte finish	3 mils / 76.2 microns	5-7 year	45°
EasyPSV® Glow							gloss finish	4.2 mils / 107 microns	indoor usage only	45°
EasyPSV® Removable							matte finish	3 mils / 76.2 microns	2-3 year clean removability	45°
EasyPSV® Chalkboard							matte finish	5 mils / 127 microns	1 year clean removability	45°

Please test for compatibility on your surface before committing to decoration
Not recommended for use with dishwasher or microwave